



HDS 12/14-4 ST

Stationary diesel-fired high performance hot water high-pressure cleaner

















- 1 Water-cooled 4-pole electric motor (oil-heated)
- Long service life.
- Improved efficiency.

- 3 Water treatment unit
- Truckwash

2 Innovative burner technology

- High heat output.
- Spiral heating coil for a compact design.

4 Water treatment unit

■ Truckwash

TECHNICAL DATA AND EQUIPMENT.





HDS 12/14-4 ST

- Integral pressure relief system
- SDS system
- Dry running protection

Technical data		
Order Number		1.699-921.0
EAN code		4054278169521
Current type	Ph/V/Hz	3 / 400 / 50
Fuse protection	Α	min. 20
Flow rate	I/h	600-1200
Pressure	bar / MPa	30-140 / 3-14
Max. temperature	°C	155 / 80
Power rating	kW	7,5
Consumption, heating oil/gas	kg/h	7,3
Weight	kg	160
Dimensions (L x W x H)	mm	1110 × 565 × 700

Equipment			
SDS system			
System pressure relief	•		
Flame monitor			
Ready for Servo Control			
Ready for remote control			

■ Included in delivery.























				1					
		Ouden Nomber	ID.	Max. working	Lamath		···	Becaulation	
		Order Number	טו	pressure	Length	P	Price	Description	Ш
Standard with unions on both sides	1			1					
High-pressure hose, 15 m DN 10, 220 bar, extension	1	6.110-042.0	ID 10	220 bar	15 m			15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	•
High-pressure hose, 20 m DN 10, 220 bar, extension	2	6.110-043.0	ID 10	220 bar	20 m			with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	•
High-pressure hose, 25 m DN 10, extension, not rotatable	3	6.110-044.0	ID 10	220 bar	25 m				A
Hose assembly premium DN12 21MPa 15m	4	6.110-059.0	ID 12	250 bar	15 m			High-pressure hose for water volumes greater than 1,800 l , h. With union on both sides. 2x M 22 x 1.5 with anti-kink	A
Hose assembly premium DN12 21MPa 40m	5	6.110-060.0	ID 12	250 bar	40 m			protection.	A
Longlife 400 with unions on both si	ides			L				I.	
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling		6.110-023.0	ID 8	400 bar	30 m			With rotary coupling, 2 x M 22 x 1.5	•
High-pressure hose Longlife 400, 20 m, DN 8, extension	7	6.110-027.0	ID 8	400 bar	20 m			with rotary coupling, 2 x M 22 x 1.5	A
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	8	6.110-029.0	ID 8	400 bar	15 m			With rotary coupling, 2 x M 22 x 1.5	A
High-pressure hose 1.5 m, DN 8, including connectors	9	6.110-024.0	ID 8	400 bar	1,5 m			1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
	10	6.110-069.0	ID 8	400 bar	1,5 m			(
High-pressure hose packaged	11	6.110-038.0	ID 8	400 bar	10 m				
Food industry version with unions	on bot	h sides							
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	12	6.110-051.0	ID 8	250 bar	10 m			10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	•
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	13	6.110-052.0	ID 8	250 bar	20 m			20 m high-pressure hose (DN 8) with swivel coupling, Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	A
Longlife food industry version with	union	s on both sides							
High pressure hose food DN 8 / 10 m	14	6.110-053.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, $2 \times M$ $22 \times 1,5$	•
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	15	6.110-054.0	ID 8	400 bar	20 m			Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun- ted)	

[☐] Available accessories. ▲ Extension hose.

















								٦
		Order Number	Flow rate	Nozzle size	Diame- ter	Price	Description	
Hard surface cleaner FR 30 ME								
FR 30 ME surface cleaner	1	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<u>_</u>
Hard Surface Cleaner FR 50								
FR 50 surface cleaner	2	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	_
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 1100 - 1300 l/h	3	2.639-188.0	1100-1300 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h).	
Machine-specific nozzle kits for F	RV							
Nozzle pack 080	4	2.642-982.0		80				
Hard surface cleaner FRV 30 Me								
Suction hose FRV 30 me	5	4.441-040.0						
FRV 30 ME	6	2.111-012.0						j
Surface Cleaner FR 50 Me								
	7	2.111-024.0						

[☐] Available accessories. ▲ Extension hose.































								Т
		Order Number				Price	Description	
Nozzle union								Ť
Protection part TR only for repla-	1	4.112-011.0						Ī
cement][
Coupling parts			ı	ı				
	2	6.987-705.0] [
Rotary coupling			I	1		1	1	Т
Rotary coupling	3	4.111-021.0					Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5	
							m. With grip protection.	
Coupling								
Coupler -2xM22x1,5	4	4.111-037.0					Brass double connector for connecting and extending high-	
							pressure hoses. With rubber protection. Connector: 2x M 22	2 [
Commenter							x 1.5 m.	_
Connector Nozzle connector/screw connector	5	4.111-022.0	I		ı	I	Nozzle connector/screw connector for connecting high-	Т
NOZZIE COIIIECTOI/SCIEW COIIIECTOI	כ	4.111-022.0					pressure nozzles and accessories to the high-pressure trig-	1.
							ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5	
							and 1x M 18 x 1.5.	
	6	4.111-038.0						[
Adapter EASY!Lock			1					
Adapter 1 M22AG-TR22AG	7	4.111-029.0						[
Adapter 2 M22IG-TR22AG	8	4.111-030.0						[
Adapter 3 M22IG-TR22AG	9	4.111-031.0						[
Adapter M22 - Swivel	10	4.111-032.0					M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the	
							telescopic lance with a high-pressure hose with AVS connec	- 11
							tion.	
Adapter 5 TR22IG-M22AG	11	4.111-033.0						[
Adapter 6 TR22IG-M22AG	12	4.111-034.0						[
Adapter 7 M18IG-TR20AG	13	4.111-035.0						[
Adapter 8 TR20IG-M18AG	14	4.111-036.0						[
HP detergent injector			ı					
Detergent injector for high and	15	4.637-032.0					Detergent injector for independent high and low pressure	
low pressure (without nozzles) Detergent injector for high pressu-	16	4.637-033.0					dosage. Maximum dosage about 15%. Cleaning agent dosage at high pressure 3 - 5 %	+
re	10	4.037-033.0					Cledillig agent dosage at high pressure 3 - 5 %	[
Machine-specific nozzle kit with or	der no	. 3.637-170	I.	'				_
Machine-specific nozzle kit with	17	4.769-048.0					For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HF	2
order no. 3.637-170.0 1000-1200							power nozzle + union	1
I/h I/h								Ţ
Nozzle insert with order no. 3.637-	i i		1				La	-
Nozzle insert for Order No. 3.637-	18	4.769-003.0					Nozzle insert for detergent injector 3.637-001 for high-	
001, high-pressure for machines up to 1100 l/h.							pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	[
Low pressure for units rated up to	19	4.769-001.0					For low pressure with machines up to 1.100 l/h	+
1100 l/h								

[☐] Available accessories. ▲ Extension hose.





		1		1			
		Order Number	Nozzle size			Price	Description
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	1	2.113-038.0	80				High-pressure nozzle with powerful jet for extremely stubborn dirt.
Power nozzle spray angle 15°							
Power nozzle spray angle 15°	2	2.113-051.0	80				Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
Power nozzle spray angle 25°							
Triple nozzle, touchless changeover	3	2.113-015.0	80				
Power nozzle spray angle 40°							
Power nozzle spray angle 40°	4	2.113-057.0	80				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[☐] Available accessories. ▲ Extension hose.











								.
								.
		Order Number	Flow rate			Price	Description	
Trigger guns		<u>'</u>	<u>'</u>	<u> </u>	'			
Extended easy press trigger gun	1	4.118-005.0					Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.	
Servo Control								
Servo control	2	4.118-009.0	1100 l/h					
Quick connect								
Quick-fitting pipe union coupler	3	2.115-000.0						ıпl
trapezo								اتــ
Quick-fitting pipe union plug nipp-	4	2.115-001.0						пΙ
le tra								

[☐] Available accessories. ▲ Extension hose.







		Order Number	Max. working pressure	Nozzle size		Price	Description
Angle vario nozzle 0°-90° Variable angle nozzle 0-90°	1	4.113-006.0		80			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
Dirt blaster, large Dirt blaster - without changeover function	2	4.114-030.0	300 bar	70			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

[☐] Available accessories. ▲ Extension hose.







		Order Number	Nozzle size			Price	Description
Wet blasting attachment (without r	nozzle)			1	I.		
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment						
Nozzle kit for wet blasting attachment 080	3	2.637-908.0	80				Nozzle pack for wet-blasting nozzle for items 28 / 29 Consisting of wet-blasting nozzle and nozzle insert - only in conjunction with wet-blasting attachment 4.762-010/-022
Boron carbide nozzle							
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-083.0	8 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

[☐] Available accessories. ▲ Extension hose.





		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					

[☐] Available accessories. ▲ Extension hose.













		Order Number	Flow rate		Price	Description
Cup foam lance						
Packing complete for 6.394-968.0	1	2.112-017.0				
Tank 1L	2	6.414-954.0				
Inno Foam Set						
Inno foam kit with detergent injector	3	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	4	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 110 Inno/Easy set 1000 - 1300 I/h	5	2.111-020.0	1000-1300 l/h			Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.
Foam nozzle mounting kit						
Foam nozzle kit	6	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[☐] Available accessories. ▲ Extension hose.

















		Order Number	Length			Price	Description	
Automatic, self-winding hose reels		ı			1			
Add-on kit hose reel plastics	1	6.392-074.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	2	6.392-083.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Hose reel, automatic, 20 m, painted	3	6.392-106.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose.	
	4	6.392-105.0	20 m					
Hose reel, automatic, 20 m, stain- less steel	5	6.392-076.0	20 m				Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	6	6.392-122.0	20 m				High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Swivel holder	7	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	. 🗆
ABS wall fastening stainless steel	8	2.641-867.0					Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[☐] Available accessories. ▲ Extension hose.

11

10





12

								\Box
			Max. working					
		Order Number	pressure	Length		Price	Description	
Rotating spray lances								
Lance 250 mm, non-rotatable	1	4.112-027.0	300 bar	250 mm				
550 mm lance, non-rotatable	2	4.112-024.0	300 bar	400 mm				
Rotatable lance, 600 mm, ergono-	3	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergono	_
mic mic	3	4.112 007.0	300 bai	000 11111			mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergono-	4	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergono	-
mic							mic handle for ease of use and protection. Rotatable 360°	
							under pressure.	
1050 mm lance, rotatable, ergono-	5	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo-	\Box
mic							nomic handle for ease of use and protection. Rotatable 360	
							under pressure.	
Lance 1550 mm, rotatable, ergo-	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo-	
nomic							nomic handle for ease of use and protection. Rotatable 360'	
							under pressure.	Ш
Lance 2050 mm, rotatable, ergo-	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo-	
nomic							nomic handle for ease of use and protection. Rotatable 360	
							under pressure.	Щ
Double lance								.
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on	
							handle at full water flow rate. Suitable for agricultural use (
							e.g. stable cleaning).	Щ
Angular spray lance							_	,
WC and gutter lance	9	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe-	
							cially shaped for effective and hygienic cleaning of gutters	
							and toilets.	Щ
Flexible spray lance				l.				
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to	
							140°, ideal for cleaning difficult to reach areas, e.g. gutters.	Щ
Telescopic spray lance							_	
Telescopic jet pipe	11	4.112-037.0	225 bar	5400 mm				
Restraint belt for telescopic jet	12	6.373-987.0					Convenient strap for relief when working with the telesco-	
pipe							pic spray lance (6.394-690). The burden is optimally distri-	
							buted on the body and longer periods of use are possible.	Ш
Gutter cleaner								
Gutter cleaning lance	13	2.112-015.0					The lance is suited for cleaning of gutter systems. Because	
							of the shape of the lance and the special nozzle the gutter	
							can be cleaned without removing the cover plates.	Ш
Undercarriage spray lance								
Underbody lance	14	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and	
							wheel arch cleaning. Without high-pressure nozzle.	
Additional handle								
	15	4.321-380.0						

[☐] Available accessories. ▲ Extension hose.









		Order Number	Flow rate		Price	Description	
		Order Homber	1 low rate		FIICE	Description .	
Push-on washing brush							
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple	
						nozzle. Fits on new double and triple nozzles.	
Rotating washing brush							
	2	4.113-002.0	800-1300 l/h				
	3	4.113-005.0	800-1300 l/h				

[☐] Available accessories. ▲ Extension hose.





								\Box
		Order Number	Length	Diameter		Price	Description	
Geka coupling	_	'						
Hose coupling	1	6.388-458.0					with female thread	
- · · · · · · · · · · · · · · · · · · ·								

[☐] Available accessories. ▲ Extension hose.