



KARCHER

HDS 6/14 C EASY!

Single-phase HDS 6/14 C hot water high-pressure cleaner with eco!efficiency mode, EASY!-Force trigger gun and Servo Control, the infinitely variable pressure and water flow regulation function from Kärcher.







1 Economical

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

2 Ease of use

- Intuitive operation with one-switch control.
- Intuitive operation with large single-button selector switch.



3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
 Change land back for nonzero and back back accessory back
- Storage hooks for power cord and high-pressure hose.
- 4 Mobility
- Jogger" design with large wheels and castors.
- Large integrated handles in the chassis.

TECHNICAL DATA AND EQUIPMENT

KÄRCHER



HDS 6/14 C EASY!

Economical eco!efficiency mode
Convenient one-button operation
Extensive standard equipment

Technical data		
Order No.		1.169-903.0
EAN code		4054278167190
Type of current	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	240-560
Pressure	bar / MPa	30-140 / 3-14
Max. temperature	°C	80 / 155
Power rating	kW	3,6
Fuel oil consumption, full load	kg/h	3,5
Fuel tank	I.	15
Weight	kg	93
Dimensions (L x W x H)	mm	1060 × 650 × 920
Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / ID 6, 250 bar
Spray lance	mm	840
Power nozzle		1
SDS system		1 · · · · · · · · · · · · · · · · · · ·
Anti-twist system		·
Pressure cut-off		1
Integrated fuel and cleaning agent t	tank	1
Servo Control		-
Included in delivery.		

HDS 6/14 C EASYI, 1.169-903.0, 2017-03-09

KARCHER





17-18











1-3, 19





5-6

2

	1							—
		Order No.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides	5				II			1
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	-
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	-
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 8/155°C/315 bar.	-
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protec- tion. NW 10/155°C/220 bar	
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	250 bar	15 m		High-pressure hose for water volumes greater than 1,800 l h. With union on both sides. 2x M 22 x 1.5 with anti-kink	/
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	250 bar	40 m		protection.	
High-pressure hose, 10 m DN 6,	11	6.110-035.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection.	
AVS trigger gun connector	12	6.110-034.0	ID 6	250 bar	10 m		With patented rotating AVS trigger gun connector and manu al coupling. Further data: DN 6/155°C/250 bar.	/- [
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- tion	13	6.110-056.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (piv- ot-mounted) and hand screw union. M 22 x 1.5 with an- ti-kink protection. NW 6/155°C/300 bar	
Longlife 400 with unions on both s	ides							
High-pressure hose Longlife 400, 30 m ID 8, including rotary cou- pling	14	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 20 m, ID 8, extension	15	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 15 m, ID 8, including rotary cou- pling	16	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose 1.5 m, ID 8, including connectors	17	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
	18	6.110-069.0	ID 8	400 bar	1,5 m			
High-pressure hose packaged		6.110-038.0	ID 8	400 bar	10 m			
Food industry version with unions		1	1	1				
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	20	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	
High-pressure hose, 20 m ID 8, suitable for food industry, exten- sion piece	21	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	



		Order No.	ID	Max. working pressure	Length		Price	Description
Longlife food industry version with	union	s on both sides						
High pressure hose food ID 8 / 10 m	22	6.110-053.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate- rial. With rotary coupling, 2 x M 22 x 1,5
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	23	6.110-054.0	ID 8	400 bar	20 m			Longlife HP hose for use in the food industry. Außen- decke## animal-grease-resistant, non-colour-bleeding mate- rial. With patented AVS connection in the pistol (pivot mounted)
Food industry version					· · · · ·	· · · ·		
High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	24	6.110-063.0	ID 6	250 bar	15 m			15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.
Special hoses								
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	25	6.110-068.0	ID 8	400 bar	1,5 m			[

KARCHER

ACCESSORIES FOR HDS 6/14 C EASY! 1.169-903.0



		Order No.	Flow rate		Price	Description	
Trigger guns			1	1	1	I	
Extended easy press trigger gun	1	4.118-005.0				Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.	
Servo Control						· · ·	
Servo control	2	4.118-007.0	0-750 l/h			Servo control for water flow and pressure control (< 750 l/h) on trigger gun.	
Quick connect							
Quick-fitting pipe union coupler trapezo	3	2.115-000.0					
Quick-fitting pipe union plug nip- ple tra	4	2.115-001.0					

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill A Extension hose.$



		Order No.	Nozzle size			Price	Description
Power nozzle spray angle 25°							
Power nozzle spray angle 25°	1	2.113-005.0	36				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °O	2	2.113-001.0	40				High-pressure nozzle with powerful jet for extremely stub- born dirt.
Power nozzle spray angle 15°							
Power nozzle 15036 - nur fuer Ersatz	3	2.113-043.0	36				
Power nozzle spray angle 40°							
Power nozzle spray angle 40°	4	2.113-003.0	40				Power nozzle with a 40° spray angle and fan jet, suitable for \Box large areas and sensitive surfaces.
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.	 		

1,5 2	3	4	6	7	8
9 10	11	12	13	14	15
	Max. working				

		Order No.	Max. working pressure	Length		Price	Description	
Rotating spray lances		,						_
1050 mm lance, rotatable, ergo- nomic	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm				
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm				
Rotatable lance, 600 mm, ergo- nomic	4	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	• □
Lance 850 mm, rotatable, ergo- nomic	5	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	•
Lance 1550 mm, rotatable, ergo- nomic	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 2050 mm, rotatable, ergo- nomic	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Double lance								
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance								
WC and gutter lance	9	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance								
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance		_	1	1				
Telescopic jet pipe	11		225 bar	5400 mm				
Restraint belt for telescopic jet pipe	12	6.373-987.0					Convenient strap for relief when working with the telescop- ic spray lance (6.394-690). The burden is optimally distrib- uted on the body and longer periods of use are possible.	
Gutter cleaner								
Gutter cleaning lance	13	2.112-015.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance							× · · · ·	
Underbody lance	14	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Zusatzhandgriff				1	1	1		
	15	4.321-380.0						
Weed control			1	1	1	1		1-
WR 50 trapezoidal thread		2.114-013.0 2.114-014.0					_	
WR 20 trapezoidal thread								



		Order No.				Price	Description
Crane lifting kit					 		
Add-on kit suspension crane HDS C	1	2.642-638.0					
Flame monitoring attachment kit							
ABS flame monitor for HDS C	2	2.642-711.0					
Y distributor							
Y distributor	3	4.111-024.0					
■ Included in delivery. □ Ava	ilable	e accessories.	▲ Extension ho	ose.			

KARCHER



		Order No.	Flow rate	Nozzle size	Diame- ter	Price	Description
Hard Surface Cleaner FRV 30							
Add-on kit hose attachment	1	2.642-528.0					
Add-on kit dirt trap	2	2.642-532.0					
Hard surface cleaner FR 30 ME							
FR 30 ME surface cleaner	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Machine-specific nozzle kit for FR							
Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h	4	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).
Machine-specific nozzle kits for FRV	/						
Nozzle kit 040 for FRV 30	5	2.642-431.0		40			
FRV 30 Me surface cleaner							
Suction hose FRV 30 me	6	4.441-040.0					
FRV 30 ME	7	2.111-012.0					

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

KARCHER

ACCESSORIES FOR HDS 6/14 C EASY! 1.169-903.0

2			Ð	5	Jure 10	6				
9	9			12		13			15-16)
		Order No.					Price	Description		
Nozzle union Protection part TR only for re-	1	4.112-011.0								
placement Coupling parts										
	2	6.987-705.0								1
Rotary coupling Rotary coupling	3	4.111-021.0							vents twisting and kinking of e of use. Connector M 22 x 1.5	
Coupling					1		1	1		
Coupler -2xM22x1,5	4	4.111-037.0							ubber protection. Connector: 2x	<
Connector								M 22 x 1.5 m.		-
Nozzle connector/screw connector	5	4.111-022.0						sure nozzles and accessorie	nector for connecting high-pres s to the high-pressure trigger . Connectors: 1x M 22 x 1.5 and	
	6	4.111-038.0								_
Adapter EASY!Lock	7	4 1 1 1 0 20 0			1 1		1	1		
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	7	4.111-029.0 4.111-030.0						_		
Adapter 3 M22IG-TR22AG	9	4.111-031.0						-		
Adapter M22 - Swivel	10							high-pressure hoses with A	l connection. For extension of VS connection or for usage of th -pressure hose with AVS connec	
Adapter 5 TR22IG-M22AG	11	4.111-033.0								-
Adapter 6 TR22IG-M22AG		4.111-034.0								
Adapter 7 M18IG-TR20AG		4.111-035.0						-		
Adapter 8 TR20IG-M18AG HP detergent injector	14	4.111-036.0								_
Detergent injector for high pres- sure	15	3.637-170.0						Cleaning agent dosage at his	gh pressure 3 - 5 %	
Detergent injector for high and low pressure (without nozzles)	16	4.637-032.0						Detergent injector for indep dosage. Maximum dosage al	endent high and low pressure bout 15%.	
Detergent injector for high pres- sure	17	4.637-033.0						Cleaning agent dosage at his		
Machine-specific nozzle kit with ord	der no	. 3.637-170			<u> </u>					
Machine-specific nozzle kit with order no. 3.637-170.0 HD 500- 700 I/h	18	4.769-046.0						For HDS 500 - 700 l/h. Cons nozzle + union	sists of nozzle insert + HP powe	er
Nozzle insert with order no. 3.637-0	001	I	I	I	1		1	I		
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.		4.769-003.0						Nozzle insert for detergent high-pressure detergent app cleaners with a water flow r	olication. For high-pressure	
Low pressure for units rated up to 1100 l/h	20	4.769-001.0						For low pressure with mach		

HDS 6/14 C EASYI, 1.169-903.0, 2017-03-09

KARCHER



		Order No.	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Barrel and tank cleaning							1	
Barrel cleaner BC 14/12	1	2.112-020.0					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment per- formance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.	t
Pipe cleaning hose, ID 6		_						
Hose assembly TR pipe cleaning DN6 max.2	2	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	3	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	4	6.110-047.0	250 bar					
Pipe cleaning nozzle							• •	
Drain cleaning dirt blaster D 25/040	5	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Drain cleaning dirt blaster D 30/040	6	6.415-946.0		40	30 mm		necessary forward movement, as well as convenient han- dling.	
Drain cleaning dirt blaster D 35/040	7	6.415-948.0		40	35 mm			
Nozzle pipe cleaning size 120	8	5.763-089.0		120	16 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	9	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	t 🗆
	10	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	11	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	t
Rotating pipe cleaning nozzle	12	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	



		Order No.	Max. working pressure	Nozzle size		Price	Description
Angle vario nozzle 0°-90°							
Variable angle nozzle 0-90°	1	4.113-006.0		80			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
Dirt blaster, large							
Dirt blaster 04	2	4.114-041.0	300 bar	40			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



		Order No.	Nozzle size		Price	Description	
Wet blasting attachment (without n	ozzle)		-				-
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attach	ment						
Nozzle kit for wet blasting attach- ment 040	3	2.637-900.0	40			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kårcher wet blasting attachment per- formance. Only in combination with wet blasting attachment 4.762-010/-022.	
Boron carbide nozzle							
Boron carbide nozzle, for ma- chines as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

KARCHER



		Order No.	Flow rate		Price	Description
Cup foam lance			-			
Packing complete for 6.394-969.0	1	2.112-018.0				
Tank 1L	2	6.414-954.0				
Inno Foam Kit				·		
Inno foam kit with detergent injec- tor	3	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and
Inno foam kit	4	2.112-008.0				stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	5	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and
Easy foam set	6	2.112-011.0				disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 090 Inno/Easy kit 700 - 1000 I/h	7	2.640-688.0	700-1000 l/h			Nozzle kit contains Kärcher power nozzles and nozzle in- serts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.
Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h	8	2.111-018.0	600-700 l/h			Optimal adaptation to different machine outputs for eco- nomic use.
Foam nozzle mounting kit						
Foam nozzle kit	9	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.

KARCHER

				4	5		
		Order No.	Length			Price	Description
Hose reel add-on kit							
Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C	1	2.110-010.0	20 m				
Automatic, self-winding hose reels							
Add-on kit automatic hose reel HDS-C	2	2.110-012.0	20 m				
Add-on kit hose reel	3	2.110-013.0					
Add-on kit hose reel plastics	4	6.392-074.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	5	6.392-083.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic.
Hose reel, automatic, 20 m, paint- ed	6	6.392-106.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
Add-on kit hose reel lacquered basaltgra	7	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stain- less steel	8	6.392-076.0	20 m				Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	9	6.392-122.0	20 m				High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Swivel holder	10	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel	11	2.641-867.0					Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.



		Order No.	Flow rate			Price	Description	
Push-on washing brush					 			
Push-on wash brush, M 18 x 1.5 $$	1	4.113-001.0					Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush								
Washing brush rotary	2	4.113-004.0	500-800 l/h					
	3	4.113-003.0	500-800 l/h					
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.				

KARCHER



		Order No.	Length	Diameter		Price	Description			
Geka coupling				-						
With hose nozzle, R 1/2"	1	6.388-461.0					with hose liner	E		
With hose nozzle, R 3/4"	2	6.388-455.0						E		
With hose nozzle, R 1"	3	6.388-465.0						E		
Hose coupling	4	6.388-458.0					with female thread	Ε		
Suction filter										
Water filter	5	6.414-956.0						E		
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	٢		
Fine-mesh water filter										
Fine-mesh water filter with adapt- er	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles con- tained in the water. Water flow rate up to 1200 l/h. Connec- tion 3/4", with adapter, 1".	_		
Fine-mesh water filter, 100 µm, R 1"	8	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pres- sure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	[
Water supply hose										
Water supply hose	9	4.440-038.0	7,5 m				NW 13 R1" / R 3/4", up to 30 °C	Ε		
	10	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	Γ		

■ Included in delivery. □ Available accessories. ▲ Extension hose.



SWEEPEX AUSTRALIA

2/5 Clay Place EASTERN CREEK NSW 2766 sweepex.com.au | sales@sweepex.com.au

1800 680 337

